



FAP PORTABLE AGITATOR



YOUR SOLUTION PARTNER



FAP PORTABLE AGITATOR

APPLICATION


- FAP series agitators are vertical direct motor-driven agitators with clamp.
- High-speed agitation is used in the food processing, cosmetics, pharmaceutical or chemical industries.

WORKING PRINCIPLE

- These agitators are fixed to the wall of the tank by means of a clamp
- Thanks to the joint, they can be inclined to the use position.
- The rotation of the propeller makes the fluid flow to do bottom of the tank and then up to the surface of the fluid along the tank wall opposite to the wall to which the agitator is fitted.
- This effect is promoted if the bottom of the tank is curved.

OPTIONS

- Motor cover
- Atex motor
- Motors: 1000 rpm or 1500 rpm
- Geared motors or variable speed drives
- Saw tooth impeller



Saw Tooth



Line Flux

MATERIALS


- Parts in contact with the media : AISI 316L
- Retainer : NBR
- Bearing support : Aluminum

DESIGN AND FEATURES

- Agitator with clamp.
- Bearing support.
- IEC B14 MOTORS, 1500 rpm, IP 55, F-class insulation.
- Maximum power 0,75 kW.
- Lineflux propeller

DIMENSIONS									
TYPE		A	B	E	F	Ø d	L max	C max	H
FAP 15-007-130	30	90	290	180	124	16	1250	234	130
FAP 10-005-130	30	90	290	180	124	16	1250	360	130

CAPACITY				
TYPE	Capacity (m3)	Power (kw)	Speed (rpm)	Weight (kg)
FAP 15-007-130	0,8	0,75	1500	16
FAP 10-005-130	0,7	0,55	900	16,5





Marfil Group Sp. Z o.o. spółka komandytowa

Ul. Chełmżyńska 70 04-247 Warsaw / Poland

Mobile: +48 506 197 962 - **Phone:** +48 22 610 19 82

info@flussmann.com - www.flussmann.com